

U.S Department of Labor
MATERIAL SAFETY DATA SHEET

Manufacturer's Name: Mercury Adhesives LLC Emergency Telephone Number: 1-800-424-9300
Address: 6150 parkway North Dr Cumming GA 30040
Chemical name and synonyms: ETHYL Trade name and synonyms: Mercury M5T, M300M, M1100G
Chemical family: CYANOACRYLATE ESTER Formula: N/A
Flammability: MEDIUM Health: MEDIUM Reactivity: MEDIUM Specific Hazard: SKIN BONDING & BURNING

SECTION II-HAZARDOUS INGREDIENTS

Hazardous Mixtures of Other Liquids, Solids, or Gases

	CAS NO.	%	CARCINOGEN		
			NTP	IARC	OSHA
ETHYL CYANOACRYLATE	7085-85-0	85-90	NO	NO	NO
POLY (METHYL METHACRYLATE)	9011-14-7	10-15	NO	N/A	NO
HYDROQUINONE	123-31-9	0.1-0.5	NO	N/A	NO

SECTION III-PHYSICAL DATA

Boiling point: More than 300-F Specific Gravity: 1.08
Vapor Pressure: Less than 0.2mm Percent Volatile, by volume: 87.2%
Vapor Density: Approximately 3 Evaporation Rate: N/A
Solubility in Water: Polymerized by water Odor: Sharp, irritating
Appearance: Clear liquid _____

SECTION IV-FIRE AND EXPLOSION HAZARD DATA

Flash Point: 185F (method used-T.O.C.) Flammable Limits: LEL: N/A UEL: N/A
Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM.
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS.
Unusual Fire and Explosion Hazards: POSSIBLE EXOTHERMIC REACTION LEADING TO SUBSTRATE IGNITION AND FUME GENERATION.

SECTION V-HEALTH HAZARD DATA

Threshold Limit Value: NO CRITERIA FOR MEASUREMENT. NOT YET ESTABLISHED. ESTIMATED 2PPM.
Effects of Overexposure: VAPOR IS IRRITATING TO EYES AND MUCOUS MEMBRANES ABOVE TLV. PROLONGED AND REPEATED OVEREXPOSURE TO VAPORS MAY PRODUCE ALLERGIC REACTIONS WITH ASTHMA-LIKE SYMPTOMS IN SENSITIVE INDIVIDUALS.
Emergency and First Aid Procedures: SKIN: IMMERSE BONDED SURFACE IN WARM SOAPY WATER. PEEL OR ROLL SURFACE APART WITH AID OF BLUNT EDGE. DO NOT PULL APART WITH DIRECT OPPOSING ACTION. EYE: FLUSH WITH WARM WATER AND APPLY GAUSE PATCH. EYE WILL OPEN WITHIN 1-4 DAYS. MOUTH: APPLY WARM WATER TO MOUTH. PEEL OR ROLL LIPS APART. BURNS: SHOULD BE TREATED NORMALLY AFTER THE LUMP OF CYANOACRYLATE IS RELEASED FROM THE TISSUE. INHALATION: REMOVE TO FRESH AIR.

SECTION VI-REACTIVITY DATA

Stability: STABLE (UNDER NORMAL CONDITIONS). Conditions to avoid: AMINES, BASIC MATERIALS.
Hazardous Decomposition Products: NONE. Hazardous Polymerization: WILL NOT OCCUR.
Incompatibility (Materials to avoid): POLYMERIZED BY CONTACT WITH WATER, ALCOHOL, AMINES, ALKALIES.

SECTION VII-SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled: FLOOD WITH WATER TO POLYMERIZE. SOAK UP WITH AN INERT ABSORBENT.
Waste disposal method: POLYMERIZE AS ABOVE. INCINERATE IN ACCORDANCE WITH EPA AND LOCAL REGULATIONS.

SECTION VIII-SPECIAL PROTECTION INFORMATION

Respiratory protection (type): NONE NEEDED FOR NORMAL USE.
Ventilation: POSITIVE DOWN-DRAFT EXHAUST VENTILATION SHOULD BE PROVIDED TO MAINTAIN VAPOR CONCENTRATION BELOW TLV.
Protective Gloves: POLYETHYLENE GLOVES, DO NOT USE COTTON GLOVES.
Eye Protection: SAFETY GLASSES OR GOGGLES.
Other protective equipment: POLYETHYLENE/POLYPROPYLENE COATS OR APRONS (NOT RUBBER OR COTTON).

SECTION IX-SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage: STORE AT OR BELOW 75-F TO MAXIMIZE SHELF LIFE.
Other precautions: AVOID CONTACT WITH SKIN AND EYES. AVOID BREATHING VAPOR.

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability if any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to

be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material supplied by us.